

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200 Email: techinfo@norglass.com.au

Web: norglass.com.au



MICROSHIELD TRADITIONAL MARINE SPAR VARNISH

DESCRIPTION: A clear, low odour, high gloss urethane/alkyd blend with high levels of state of the art inhibitors and stabilizers for maximum exterior protection.

USES: Panelling, doors, outdoor furniture, railings, general bright work on boats and all areas not subjected to heavy traffic.

SIZES: 10litre, 4litre, 2litre, 1litre, 500ml

PROPERTIES (at 20°C)

COLOUR: Light Amber

TOXICITY: See Precautions and refer to Safety Data Sheet

FINISH: High Gloss

COVERAGE: Up to 12m² per litre

DRYING TIME: Touch dry in 3 hours

RECOATING: After 16 hours at 50% relative humidity

POT LIFE: N/A

MIXING RATIO: N/A

THINNING: Not normally recommended, but up to 5% Weatherfast Brushing Thinner can be added to improve flow in hot weather. Use up to 20% Weatherfast Spraying Thinner when spraying.

WEIGHT/LITRE: 0.900kg

VOLUME SOLIDS: 55%

FLASH POINT:	32°C
CLEAN UP:	WEATHERFAST BRUSHING THINNER
U.N. NUMBER:	1263
TRANSPORTATION:	DG Class: 3 HAZCHEM: 3Y P.G. III
PREPARATION:	New Bare Timber must be dry, well sanded and have the dust particles within the grain removed by paper towel soaked in NORCLEAN-PLUS. Previously varnished timber (in good condition) should be sanded thoroughly to a flat state then wiped over with a paper towel dampened with NORCLEAN-PLUS. Cracked or peeling varnishes must be totally removed back to a clean dry timber state.
APPLICATION:	The first coat should be applied by brush to work the product into the timber surface. Thinning the first coat is not normally recommended, but if carried out, care must be taken to allow additional time for drying due to the added solvents (24hrs minimum). Very light sanding (with the grain) between a further 3 coats should be a reasonable base structure for finishing. Following this, a minimum of a further 2 coats should be considered essential where exposed to long periods of sunlight.
PRECAUTIONS:	Wear protective clothing and equipment. Keep away from heat, sparks, open flames or hot surfaces. No smoking. Use only non-sparking tools. Take action to prevent static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe dust, fume, gas, mist or vapours. Wash hands thoroughly after handling. Store locked up, in a well-ventilated place. Keep cool. Keep out of reach of children
SPECIAL INSTRUCTIONS:	N/A
FIRST AID:	If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 131126 or (NZ) 0800 764 766 and have label information ready. If in Eyes rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. If eye irritation persists get medical advice. If on Skin wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs get medical advice/attention. If Swallowed rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention. If Inhaled remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.