

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200 Email: techinfo@norglass.com.au

Web: norglass.com.au



WEATHERFAST HEAT SAFE

DESCRIPTION:	A heat resistant, self-priming paint to be used in areas that are subjected to heat.
USES:	A heat resistant paint barrier for Stoves, BBQ's and oven surrounds.
SIZES:	1litre, 500ml, 250ml & 300g Spray Can
PROPERTIES (at 20°C)	
COLOUR:	Black
TOXICITY:	See precautions and refer to Safety Data Sheet
FINISH:	Semi-Gloss
COVERAGE:	Approx 16sqm per litre
DRYING TIME:	3-4 hours (touch dry after 1 hour)
RECOATING:	After 16 hours
POT LIFE:	N/A
MIXING RATIO:	N/A
THINNING:	Weatherfast Brushing Thinners can be used to assist flow. If spraying with conventional spray gun use up to 33% by volume Weatherfast Spraying Thinners.
WEIGHT/LITRE:	1.272
VOLUME SOLIDS:	60%

FLASH POINT:	32°C
CLEAN UP:	WEATHERFAST BRUSHING or SPRAYING THINNERS
U.N. NUMBER:	1866
TRANSPORTATION:	DG Class: 3 HAZCHEM: 3Y P.G III
PREPARATION:	The area must be thoroughly clean of all surface contaminants like oil, rust scale or grease and dirt. Just prior to painting the surface should be wiped down with NORCLEAN-PLUS to remove any remaining contamination.
APPLICATION:	Stir thoroughly. Apply two coats, with a light sand between coats using 240 grit sandpaper. Wipe down with NORCLEAN-PLUS again before applying second coat. Can be applied by brush, roller or spray. When spraying with conventional spray gun use up to 33% Weatherfast Spraying Thinners.
PRECAUTIONS:	Wear protective clothing and use personal protective equipment as required Keep away from heat, sparks, open flames or hot surfaces. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fumes, mist, vapours and spray. Wash hands thoroughly after handling. Use outdoors or in a well-ventilated area. Avoid release to the environment. Store locked up, in a well-ventilated place. Keep cool. Keep out of reach of children
SPECIAL INSTRUCTIONS:	The coating must be cured for a minimum of 1 week before exposed to heat. Not suitable for BBQ hot plates or oven interiors.
FIRST AID:	If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 131126 or (NZ) 0800 764 766 and have label information ready. If in Eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice. If on Skin wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation occurs get medical advice/attention. If Swallowed rinse mouth. DO NOT induce vomiting. Give a glass of water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. If Inhaled remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.