

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200 Email: techinfo@norglass.com.au

Web: norglass.com.au



WEATHERFAST MARINE DECK PAINT

DESCRIPTION:	A hard wearing, polyurethane, low gloss, low-odour coating containing synthetic slip resistant particles.
USES:	For traffic areas with intermittent water contact or damp areas such as boat decks paths, wooden decks, stairs and floors.
SIZES:	4litre, 1litre
PROPERTIES (at 20°C)	
COLOUR:	7 standard pastel shades. Arctic White can be blended with other colours to reduce the intensity.
TOXICITY:	See precautions and refer to Safety Data Sheet
FINISH:	Low sheen
COVERAGE:	Up to 10 m ² per litre (depending on surface and profile)
DRYING TIME:	Touch dry in 2 hours at 20°C and 50% relative humidity. Allow a minimum of 24 hours before permitting general traffic use
RECOATING:	After 16 hours
POT LIFE:	N/A
MIXING RATIO:	N/A
THINNING:	Up to 5% Weatherfast Brushing Thinner in hot weather
WEIGHT/LITRE:	1.130 kg – 1.250 kg (depending on colour)
VOLUME SOLIDS:	50%

FLASH POINT:	32°C
CLEAN UP:	WEATHERFAST BRUSHING or WEATHERFAST SPRAYING THINNERS
UN NUMBER:	1263
TRANSPORTATION:	DG Class: 3 HAZCHEM:3Y P.G. III
PREPARATION:	Bare Timber: In a marine environment we recommend priming with NORSEAL EPOXY WOOD TREATMENT to seal off the bare timber. Then prime with Norglass PRI-COAT and allow to dry. For other surfaces use SHIPSHAPE PRIMER-UNDERCOAT according to directions. For raw steel or aluminium use METAL-ETCH Gel then prime with SHIPSHAPE. Unpainted concrete: must be washed with CONCRETE & CERAMIC CLEANER, hosed off and allowed to thoroughly dry before painting. Fibreglass: should be sanded, cleaned with NORCLEAN-PLUS and primed with SHIPSHAPE. Where a textured area is to be painted, scrub down slip resistant surfaces with a domestic dishwashing liquid using warm water. Hose off thoroughly with fresh water and allow to dry, wipe over with NORCLEAN-PLUS. Prime with SHIPSHAPE. Sand previously painted slip resistant surfaces with a 240 grit sandpaper, remove the dust and clean with NORCLEAN-PLUS. Sand off any unsound, flaking or powdery paint, clean with NORCLEAN-PLUS before proceeding.
APPLICATION:	Stir thoroughly before use. Confine the use of a brush to perimeters only to avoid patchiness. Where possible mask out the area to be coated with blue masking tape. Use a short nap (4-6mm) nylon or mohair paint roller for best results and apply with even strokes. 2 coats recommended. Allow a minimum of 24 hours before permitting general traffic use.
PRECAUTIONS:	Wear protective clothing and use personal protective equipment as required Keep away from heat, sparks, open flames or hot surfaces. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fumes or vapours. Wash hands thoroughly after handling. Avoid release to the environment. Store locked up, in a well-ventilated place. Keep cool. Keep out of reach of children
SPECIAL INSTRUCTIONS:	Do not use below 10°C as drying will be inhibited and moisture entrapment will likely impair the finish. Do not spray this product unless special apparatus is used to accommodate the particle size.

NOTE: Thorough stirring is essential before use due to the weight of the plastic granules (they tend to float), as they have to be dispersed into the film before applying.

FIRST AID:

If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 131126 or (NZ) 0800 764 766 and have label information ready.

If in Eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice.

If on Skin wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation occurs get medical advice/attention.

If Swallowed rinse mouth. DO NOT induce vomiting. Give a glass of water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs.

If Inhaled remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult