

PRODUCT DATA SHEET

NORGLASS LABORATORIES PTY.LTD.

A.B.N. 92 001 807 245

P.O. Box 312, Neutral Bay. NSW 2089 Australia

59 Moxon Road, Punchbowl NSW

Ph: 61 2 9708 2200 Email: techinfo@norglass.com.au

Web: norglass.com.au



WEATHERFAST POLY CLEAR (GLOSS & SATIN)

DESCRIPTION: A low odour, clear, one pack coating with excellent durability and abrasion resistance. (Read the information guide on “The Good Oil on Clear Coatings” for more information.)
Contains a high level of ultra violet screening agents making it suitable for exterior and interior use.

USES: Ideal for floors, furniture and all marine applications especially in heavy duty areas. Has very good water resistance, although not recommended for areas of constant immersion.

SIZES: 10litre, 4litre, 2litre, 1litre, 500ml, 250ml & 300g Spray Cans.

PROPERTIES (at 20°C)

COLOUR: Pale amber

TOXICITY: See precautions

FINISH: Poly clear Gloss: High gloss. Poly clear Satin: Satin

COVERAGE: Up to 12 sqm per litre

DRYING TIME: Touch dry 2 hours at 50% relative humidity

RECOATING: After 12 hours and 50% relative humidity

POT LIFE: N/A

MIXING RATIO: N/A

THINNING: Not recommended but up to 5% Weatherfast Brushing Thinner can be used in hot weather. If spraying use up to 20% Weatherfast Spraying Thinner.

WEIGHT/LITRE: 0.930kg

VOLUME SOLIDS:	55%
FLASH POINT:	32°C
CLEAN UP:	WEATHERFAST BRUSHING or SPRAYING THINNERS.
U.N. NUMBER:	1263
TRANSPORTATION:	DG Class: 3 HAZCHEM: 3Y P.G. III

PREPARATION:	Bare timber: Ensure the surface is clean, dry and well sanded. Remove all dust from the grain using a rag moistened in NORCLEAN-PLUS. Previously varnished timber: If the old coating is intact and in good condition, wash down with a paper towel dampened with NORCLEAN-PLUS and lightly sand to a dull finish. Cracked or peeling varnish must be removed back to clean timber otherwise a failure will result.
APPLICATION:	Varnishes or Clears should not normally be thinned for the first coat unless additional penetration is desired (on softwoods for example). Where thinning of the coating is carried out for this purpose, it is essential to extend the drying process for migration of the added solvents. The first 3-4 coats are best applied with a quality varnish brush allowing normal overnight drying and light sanding between coats. Subsequent coats can be applied by brush, roller or spray. The recommended roller is 4-5 mm short nap mohair or microfibre roller. Where further coats are applied at intervals of not more than 4 weeks apart, sanding of the previous coat is not necessary. However, cleaning the surface of atmospheric and other contaminants with NORCLEAN-PLUS is essential. If spraying, up to 20% of WEATHERFAST SPRAYING THINNER can be added. Brushed coats should not be thinned but up to 5% of WEATHERFAST BRUSHING THINNER may be added in hot weather.
PRECAUTIONS:	Wear protective clothing and use personal protective equipment as required Keep away from heat, sparks, open flames or hot surfaces. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fumes or vapours. Wash hands thoroughly after handling. Avoid release to the environment. Store locked up, in a well-ventilated place. Keep cool. Keep out of reach of children
SPECIAL INSTRUCTIONS:	Do not use below 10°C as drying will be inhibited and moisture entrapment will likely impair the finish. NOTE: Where an external satin finish is desired, a minimum of 3 - 4 coats of Weatherfast Poly Clear gloss must be applied prior to the final satin coat. This is to

ensure that the surface absorption has been sealed in order to provide a uniform satin film.

FIRST AID:

If poisoning occurs call a doctor or Poisons Information Centre (Aust) on 131126 or (NZ) 0800 764 766 and have label information ready.

If in Eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical advice.

If on Skin wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation occurs get medical advice/attention.

If Swallowed rinse mouth. DO NOT induce vomiting. Give a glass of water. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs.

If Inhaled remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.